

LA-UR-80-2216

MASTER

TITLE: INTERACTION OF FAR-INFRARED AND MID-INFRARED LASER
TRANSITIONS IN THE AMMONIA LASER

AUTHOR(S): L. Y. Nelson, MSNW
M. I. Buchwald
C. R. Jones

SUBMITTED TO: TOPICAL MEETING ON INFRARED LASERS

DISCLAIMER

This work was prepared as a result of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily reflect those of the United States Government or any agency thereof.

By acceptance of this article, the publisher recognizes that the U.S. Government retains a nonexclusive, royalty free license to publish or reproduce the published form of this contribution, or to allow others to do so, for U.S. Government purposes.

The Los Alamos Scientific Laboratory requests that the publisher identify this article as work performed under the auspices of the U.S. Department of Energy.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

2 f.

University of California

**LOS ALAMOS SCIENTIFIC LABORATORY**

Post Office Box 1663 Los Alamos, New Mexico 87545

An Affirmative Action/Equal Opportunity Employer

INTERACTION OF FAR-INFRARED AND MID-INFRARED
LASER TRANSITIONS IN THE AMMONIA LASER

L.Y. Nelson

Mathematical Sciences Northwest, Inc.
Bellevue, Washington 98004

M.I. Buchwald and C.R. Jones
Los Alamos Scientific Laboratory
Los Alamos, New Mexico 87545

ABSTRACT

Mid-infrared laser emission in ammonia is usually observed on a $P(J + 2)$ transition when a CO_2 laser is used to optically pump a near resonant $R(J)$ absorption feature. However, by generating simultaneous FIR ammonia laser emission in the same optical cavity, mid-infrared emission is obtained exclusively on the $P(J)$ transition.

INTERACTION OF FAR-INFRARED AND MID-INFRARED LASER TRANSITIONS IN THE AMMONIA LASER

L.Y. Nelson

Mathematical Sciences Northwest, Inc.
Bellevue, Washington 98004

M.I. Buchwald and C.R. Jones
Los Alamos Scientific Laboratory
Los Alamos, New Mexico 87545

A new pattern of mid-infrared laser emission has been observed in the optically pumped NH_3 laser. Laser emission on the conventional $12.8 \mu\text{m}$ NH_3 laser transition,¹ optically pumped by the 9R16 CO_2 line, has been completely quenched and replaced by emission at $12.2 \mu\text{m}$.


Figure 1 presents an energy level diagram for NH_3 and the relevant rotational states for optically pumping the aR(6,0) NH_3 transition with the 9R16 CO_2 laser line. Recently there have been reports in the literature^{2,3} of additional NH_3 laser transitions observed at $12.08 \mu\text{m}$ (sP(7,0)) and $12.2 \mu\text{m}$ (aP(6,0)).

We have demonstrated the necessity of simultaneous FIR laser oscillation to produce laser action on the $12.2 \mu\text{m}$ transition. Several optical cavity configurations were used to study the laser process. In the simplest arrangement the CO_2 laser pump is injected into the ammonia cavity through a small hole in the entrance mirror. Ammonia emission is coupled out through this same opening or through a hole in the rear mirror. Both mirrors are mounted internally at the ends of a copper or stainless steel tube.

Figure 2 illustrates the pressure and threshold-time behavior of the $12.2 \mu\text{m}$ and $12.8 \mu\text{m}$ NH_3 laser transitions. For these measurements a Lumonics (Model 103) TEA laser with an output energy of 250 mJ on 9R16 was used. Figure 2a shows the CO_2 laser pulse shape (200 nsec/div). As shown in Figure 2b, at low pressures (0.3 torr), both the $12.2 \mu\text{m}$ and $12.8 \mu\text{m}$ ammonia laser transitions were present. The intensity ratio (12.2/12.8), of the lines was 0.01. At low pressures, the total pulse duration for the $12.2 \mu\text{m}$ line was 2 μsec and 1 μsec for relative intensity of the two lines changed to 0.5, and the duration of the $12.8 \mu\text{m}$ line was reduced to 200 nsec, while the $12.2 \mu\text{m}$ pulse duration remained about 2 μsec . For pressures greater than 1 torr, up to the highest NH_3 pressure (30 torr) where laser emission was observed, only the $12.2 \mu\text{m}$ line was observed. Figure 2d shows the $12.2 \mu\text{m}$ pulse shape at 1.3 and 10 torr.

A 12.5 mm thick KCl Brewster angle window was inserted between one of the cavity mirrors and the NH_3 laser cavity. It was now found that only the $12.8 \mu\text{m}$ NH_3 transition appeared regardless of pressure or buffer gas (He or N_2) used. KCl does not transmit infrared radiation at wavelengths longer than $30 \mu\text{m}$. NH_3 FIR laser emission wavelengths are in the range of 70 - $150 \mu\text{m}$ for optical pumping with the 9R16 CO_2 line^{3,4}. Hence, blocking the intracavity FIR laser emission has led to the elimination of the $12.2 \mu\text{m}$

Figure 1 of 4



79 82466

Figure 1. Relevant energy levels of NH_3 and summary of observed optically pumped mid-infrared laser transitions found in this work and in References 1, 2 and 3.

Nelson
Figure 2 of 4






Figure 2. Pulse shapes and relative time histories of the CO_2 pump and NH_3 laser transitions. Onset time of CO_2 laser pulse is indicated by an arrow for each trace. Time scale is 200 nsec/division.



(a) TOP - NH_3 - 12.2 μm
 BOTTOM - CO_2 - 9.29 μm
 200 nsec/div
 1.8 torr NH_3



(b) TOP - TOTAL FIR
 BOTTOM - CO_2
 200 nsec/div

79 82997

Figure 3. Pulse shapes and time histories for the 12.2 μm NH_3 laser transition, FIR laser emission and CO_2 pump pulse.




Figure 4. Optically pumped ammonia laser mechanism suggested by present experiments.

mid-infrared laser transition.

In an ammonia laser cavity which used a Littrow grating as a dichroic beamsplitter for the CO₂ and ammonia lasers, we have obtained several millijoules of 12.2 μ m emission. In these studies the 12.2 μ m emission was not coincident with the gain switched 9R16 CO₂ laser pulse. Instead it overlapped the N₂-tail portion of the CO₂ laser pulse (Figure 3a). FIR emission (Figure 3b), however, followed both the gain switched peak and N₂-tail portions of the CO₂ laser. This temporal behavior of the 12.2 μ m emission is not understood at this time and may be related to excessive pump power broadening of the gain⁵.

Figure 4 presents a schematic set of energy levels relevant to the proposed laser mechanism. ν_p corresponds to the CO₂ pump laser frequency, ν_L is the mid-infrared NH₃ emission frequency, and the intermediate FIR steps are denoted as ν_{F1} and ν_{F2} . The Brewster angle window experiment demonstrates that at least one of the FIR transitions is radiative. Collisional processes may contribute to population transfer into level 2 in Figure 5. A density matrix calculation⁶ for the four wave, four level ammonia system indicates that emission at ν_L will take place near line center and in the absence of a population inversion for levels 1 and 2.

Research support from the U.S. Department of Energy is gratefully acknowledged.

REFERENCES

1. L.Y. Chang and J.D. McGee, Appl Phys. Lett. 28, 526 (1976).
2. J.J. Tsee and C. Wittig, J. Appl. Phys. 49, 61 (1978).
3. T. Yoshida, N. Yamabayashi, K. Miyazaki and K. Fujisawa, Opt. Comm. 26, 410 (1978).
4. K. Gullberg, B. Hartmann and B. Kleman, Phys. Scr. 8, 177 (1973).
5. R.L. Panock and R.J. Temkin, IEEE J. Quant. Electron., QE-13, 425 (1977).
6. S.J. Hoverson and L.Y. Nelson (unpublished work).